



# Shenzhen Absen Optoelectronic Co., Ltd.

## A99-10- Specifications

Version: V20220713

Parameter		Value
Physical Parameter	LED Type	SMD 3in1 2727
	Pixel Pitch (mm)	10
	Panel Dimensions (WxHxD)/(mm)	1600x900x118
	Pixel Per Panel	160x90
	Panel Weight (kg)	46
	Panel Material	Aluminum Profile
	Module Dimensions (WxH)/(mm)	400x300
Optoelectronic Parameter	Brightness (nit)	6000
	Refresh Rate (Hz)	≥15000
	Gray scale (Bit)	16
	Contrast Ratio	6800:1
	Color Temperature (K)	7500
	Viewing Angle (H/V) (°)	160/130
	Driving Type	1/2
	AC Operating Voltage (V)	100~240
	Power Consumption (Max./Avg.)(W/m <sup>2</sup> )	650/217
Application Parameter	Storage Temperature (°C)	-40~+60
	Operating Temperature (°C)	-20~+50
	Storage Humidity (RH)	10%~90%
	Operating Humidity (RH)	10%~90%
	IP Rating (Front/Rear)	IP65/IP65
	Module Maintenance	Front or Rear
	PSU & Others Maintenance	Rear
	Panel Installation Type	Fixed
	Max Rigging QTY.	/
	Certificate	TUV,CE

Remark: Power consumption tolerance: ±15%, according to the actual situation.

SHENZHEN ABSEN OPTOELECTRONIC CO.,LTD 2001-2022 ALL RIGHTS RESERVED