1.5



FAST. RELIABLE. ACCURATE. MISSION-CRITICAL READY.

- 16:9 Aspect Ratio Panel
- 4 Panels = 55" Display
- Exceptional Grayscale
- Wide Viewing Angle
- Dual Power Supplies
- Dual Receiving Cards
- Rear Serviceable
- VESA-Mount Compatible

13.2 lb

110%
COLOR GAMUT

Aluminium Alloy

CABINETS









DESIGNED FOR CONTROL CENTER ENVIRONMENTS

- Fine mounting adjustments on every panel for a perfect installation
- Space-saving thin profile design has side-mounted data and power ports
- · Center and side handles for ease of handling and installation



UNPARALLELED IMAGERY

- High grayscale, even at low brightness levels
- Broadcast ready with high refresh rates
- Broad color gamut for stellar image accuracy
- Mullion-free Displays

FIT FOR THE JOB

- 16:9 aspect tiles create true HD, 4K or 8K screens
- 27.5" lightweight die cast aluminum frames for strength



SPECIFICATIONS	CR1.2	CR1.5	CR1.9
PIXEL PITCH	1.25 mm	1.58 mm	1.91 mm
PIXEL CONFIGURATION	3-in-1 SMD		
PANEL SIZE (WxHxD)		24" x 18" x 3"	
	610 x 343 x 67 mm		
CABINET MATERIAL	Aluminum Alloy		
PANEL WEIGHT	13.2 lb / 6 kg		
PIXEL MATRIX PER PANEL (WxH)	480 x 270 pixel	384 x 216 pixel	320 x 180 pixel
IP RATING (FRONT/REAR)	IP40 / IP21		
VIEWING ANGLE (H/V)	160° / 140°		
BRIGHTNESS	600 nits	700 nits	800 nits
REFRESH RATE	3,840 Hz or 1,920 Hz		
GRAYSCALE	13 bit or 14 bit		
CERTIFICATIONS	CE, ETL, FCC		

*All Specifications are subject to change without notice. Absen Affinity™ results may vary.

