

# DATA SHEET

## APPRIMO TOUCH 10 TOUCH PANEL



The Apprimo Touch 10 is a 10" touch panel for any room that requires a more complex level of control, while still being a stylish and discreet interface that fits in any type of interior design. It is PoE powered and includes PIR sensors that turn the screen on automatically and adjusts the screen brightness based on the ambient light level of the room. The user interface is fully configurable with Project Designer software, which includes several themes and customizable templates to choose from. The Apprimo Touch 10 is operated by a separate controller, allowing you to customize a solution that perfectly matches the customer requirements.

### FEATURES

- 10" capacitive touch LCD interface
- Scratch-resistant glass
- Several UI design templates and themes available in Project Designer software
- Customizable user interface to fit customers' control requirements and corporate identity
- Can be wall-mounted or sit on a flat surface
- Fits standard single gang US, EU, and DK back boxes
- Screen turns on automatically as someone approaches
- Display brightness can adjust automatically to the ambient light level
- PoE powered (IEEE 802.3at Class 3, 15W) for simple, single CAT5e/CAT6 cable installation
- Firmware can be updated via mini USB port
- Covered by Biamp Systems' 5-year warranty


### ARCHITECTS & ENGINEERS SPECIFICATIONS

The touch panel shall utilize an Ethernet network via an RJ-45 connector for networking as well as software configuration and control. The touch panel shall include a 10" capacitive touch high contrast LCD for function selection. The touch panel shall be made from PVC/ABS material with UV protection additive. The touch panel shall include sensors that detect ambient light levels and adjust display brightness automatically. The touch panel shall be powered by PoE (IEEE 802.3at Class 3, 15W). The touch panel shall be CE marked, UL listed, and compliant with the RoHS directive. Warranty shall be five years. The touch panel shall be an Apprimo Touch 10.

## APPRIMO TOUCH 10 SPECIFICATIONS

<b>Display Type:</b>	High-Contrast Capacitive Touch LCD	<b>Overall Dimensions</b>	
<b>Display Size:</b>	10" (254 mm) diagonal	<b>Height:</b>	6.67 inches (169 mm)
<b>Display Resolution:</b>	1280x800	<b>Width:</b>	9.7 inches (246 mm)
<b>Maximum Display Brightness:</b>	350 nits	<b>Depth:</b>	1.6 inches (41 mm)
<b>Network Connection:</b>	RJ-45 with Ethernet cable (Cat 5e and above)	<b>Weight:</b>	1.2 lbs (560 g)
<b>Mini USB port:</b>	USB 2.0	<b>Included Accessories:</b>	Mounting bracket and screws Ejector Pin USB-OTG adapter Polishing cloth
<b>Sensors:</b>	Proximity Ambient Light	<b>Environmental</b>	
<b>Controller Compatibility:</b>	Impera Alfa II Impera Lima Impera Tango Impera Sierra II	<b>Ambient Operating Temperature Range:</b>	32 - 104° F (0 - 40° C)
<b>Power:</b>	PoE (IEEE 802.3at Class 3, 15W)	<b>Humidity:</b>	10-90% relative humidity (non-condensing)
		<b>Altitude:</b>	0-6,600 ft (0-2000m) MSL
		<b>Compliance:</b>	CE marked (Europe) RoHS Directive (Europe)

## OPTIONAL ACCESSORIES



**TP-TS**  
Table stand

Biamp and Apprimo are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.