



WyreStorm - Because the Technology Matters.

Introduction

The WyreStorm CAB-IR-LINK IR integration cable provides integrators with a simple bidirectional IR integration between WyreStorm products and any mainstream control system.

Simply plug the CAB-IR-LINK cable from the IR emitter output of any control system to the IR RX port of a WyreStorm matrix or extender set to achieve seamless control system compatibility and integration.

Key Features

- Compatible with most leading control systems, including: Control4, Crestron, AMX, Niles, RTI, Bitwise and WyreStorm Enado
- 1.2m (length) mono-stereo IR integration cable*
- Auto-sensing polarity
- Automatically adjusts for 5v or 12v control bus
- Tip-VCC 5V, Ring-Signal, Sleeve-Ground

In the Box

1x CAB-IR-LINK cable

Specifications

Communication and Control	
IR	1x IR In: 3.5mm (1/8in) TRS Stereo 1x IR Out: 3.5mm (1/8in) TS Mono
Environmental	
Operating Temperature	14°F ~ 122°F (-10°C ~ 50°C) 10% ~ 90%, non-condensing
Storage Temperature	-4°F to ~ 140°F (-20°C ~ +60°C) 10% ~ 90%, non-condensing
Maximum BTU	N/A
Dimensions and Weight	
Weight	0.48kg/ 1.05lbs
Cable Length (Connector to Connector)	2m/7ft

Right Product for the Right Application.

