

COLW41

Column speaker for speech 70/100V



The COLW41 offers excellent audio directivity for music as well as speech. Thanks to the elegant design, this speaker is ideal for indoor and outdoor use: from sports fields to public buildings or recreational areas, meeting rooms or educational facilities.

Apart column speakers offer the perfect combination of looks and acoustical qualities! The COLW41 has 4 x 3,3" woofers and 1 x 1" tweeter.

A standard wall bracket and installation tools are included.


The COLW41 loudspeakers can be painted in any colour.

TECHNICAL SPECIFICATIONS


height in mm	555	width in mm	100
depth in mm	83	loudspeaker system	multiple
woofer size in inch	4 x 3,3	woofer cone material	coated paper
tweeter size in inch	1	mounting system	L-brackets
colour	white	100V transformer power taps in watts	40 - 30 - 15
70V transformer power taps in watts	40 - 30 - 15 - 7	impedance (ohms)	16
low impedance dynamic power in watts	80	low impedance RMS power in watts	40
SPL 1W/1m in dB	97	max SPL 1m in dB	110
frequency response in Hz	190 - 20K	main construction material	aluminium
grille main material	aluminium	IP rating	
Horizontal dispersion angle 1000 Hz	180°	Vertical dispersion angle 1000 Hz	50°
closest RAL colour (subject to deviations)	RAL9016	Net weight product (kg)	3.9

POLAR PLOTS


Data Shown: COLW41 (Apart Audio)
Display Parameters: Frequency: 1000Hz (1/24th Octave)




Data Shown: COLW41 (Apart Audio)
Display Parameters: Frequency: 2000Hz (1/24th Octave)




Data Shown: COLW41 (Apart Audio)
Display Parameters: Frequency: 4000Hz (1/24th Octave)




Data Shown: COLW41 (Apart Audio)
Display Parameters: Frequency: 8000Hz (1/24th Octave)



MORE PICTURES



ACCESSORIES**COLWBRA**

Bracket for easy tilting and rotating of COLW sound columns