


USB-C to USBC Cable (1m/3ft) or (2m/6ft)

EXP-CAB-USBC-xM



Quickstart Guide

 WyreStorm recommends reading through this document in its entirety to become familiar with the product's features prior to starting the installation process.



In the Box

1x EXP-CAB-USBC-xM Cable

Wiring and Connections

IMPORTANT! Installation Requirements

- Follow the labeling and the diagrams for connection to ensure proper operation.

Audio and Video	
Video Resolution (Max)	1920x1080p @ 240Hz 4096x2160p @60Hz 4:4:4 10bit 4096x2160p@60Hz RGB
Audio Formats	2ch PCM
Supported Standards	RGB USB Superspeed USB Alt-Mode
Communication and Control	
USB	USB 3.2 Gen 2x2 Superspeed 20Gbps
Power	
Power Delivery	20V 5A (100w)
Environmental	
Operating Temperature	14°F ~ 158°F (-10°C ~ 70°C) 0% ~ 85%, non-condensing
Storage Temperature	-40°F ~ 185°F (-40°C ~ 85°C) 0% ~ 85%, non-condensing
Dimensions and Weight	
Length	1m/3ft 2m/6ft
Cable Diameter	0.043kg/.09lbs (1m) 0.066kg/.15lbs (2m)
Regulatory	
Safety and Emission	CE FCC RoHS EAC RCM

Note: WyreStorm reserves the right to change product specification, appearance or dimensions of this product at any time without prior notice.

Warranty Information

WyreStorm Technologies ProAV Corporation warrants that its products to be free from defects in material and workmanship under normal use for a period of two (2) years from the date of purchase. Refer to the Product Warranty page on wyrestorm.com for more details on our limited product warranty.

