

# FOX USB Extender Plus

## FIBER OPTIC EXTENDER FOR USB PERIPHERALS

- ▶ Extends USB peripherals very long distances over fiber optic cabling
- ▶ Supports USB 2.0 to 1.0 devices and USB 3.0 devices that can operate at USB 2.0 data rates of up to 480 Mbps
- ▶ Receiver features an integrated four-port hub with 5 Volts, 500 mA available on each port
- ▶ Peripheral emulation
- ▶ Real-time status LED indicators for troubleshooting and monitoring
- ▶ Compatible with FOX Series matrix switchers
- ▶ Multimode and singlemode models available



FOX T USB Extender Plus

FOX R USB Extender Plus

The Extron FOX USB Extender Plus is a transmitter and receiver set for long haul signal extension of USB signals over fiber optic cabling. The transmitter features peripheral emulation to support uninterrupted communication between the host and a USB device. For simplified integration, the receiver features a built-in, active four-port hub that supplies 5 Volts, 500 mA per port to power attached devices. These and other features make the FOX USB Extender Plus ideal for extending USB signals very long distances over fiber optic cabling.



**Extron Electronics**  
INTERFACING, SWITCHING AND CONTROL

## DESCRIPTION

The Extron **FOX USB Extender Plus** is a fiber optic transmitter and receiver set for long haul transmission of USB signals over fiber optic cabling. Engineered for reliability and exceptional performance, it uses Extron all-digital technology to deliver a perfect signal. This fiber optic extender is compatible with USB 3.0, 2.0, 1.1, and 1.0 devices with transfer data rates up to 480 Mbps, enabling bulk, control, interrupt, and isochronous transfers as defined by the USB specification. Designed specifically for AV systems, the FOX USB Extender Plus includes many integrator friendly features such as peripheral emulation, an active four-port hub that supplies 5 Volts, 500 mA per port, and real-time system monitoring. Compact, low-profile enclosures allow for discreet installation.

The FOX USB Extender Plus supports USB peripherals such as interactive whiteboards, keyboards, mice, mass storage devices, webcams, headsets and speakers, along with other USB devices in a wide variety of environments. For secure environments, the FOX USB Extender Plus HID model is designed to ensure that only authorized device types are recognized. It allows connection of a keyboard, mouse, smart card reader, hub, or similar USB device, and prevents connection of unauthorized hardware.

## KEY FEATURES

- ▶ Extends USB peripherals very long distances over fiber optic cabling
- ▶ Supports USB 2.0 to 1.0 devices and USB 3.0 devices that can operate at USB 2.0 data rates of up to 480 Mbps
- ▶ Receiver features an integrated four-port hub with 5 Volts, 500 mA available on each port
- ▶ Peripheral emulation
- ▶ Real-time status LED indicators for troubleshooting and monitoring
- ▶ Compatible with Extron FOX Matrix Switchers for signal distribution systems up to 1000x1000 and larger
- ▶ Device class filtering on select models restricts the range of device types to HID and smart card readers - FOX USB Extender Plus HID
- ▶ Available as an 850 nm multimode model for moderate-range transmissions up to 2 km (1.25 miles) and a 1310 nm singlemode model for distances up to 30 km (18.75 miles)
- ▶ Industry standard LC connectors provide reliable physical connectivity and precise fiber core alignment
- ▶ 1" (2.5 cm) high, quarter rack width metal enclosures
- ▶ Highly reliable, energy-efficient external universal power supply included

## SPECIFICATIONS

USB		
USB host support	xHCI (USB 3.0), EHCI (USB 2.0), OHCI/UHCI (USB 1.1)	
USB traffic types	Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480 Mbps)	
USB HOST – TX UNITS		
Number/signal type	1 USB	
INTERCONNECTION BETWEEN TRANSMITTER AND RECEIVER		
<b>NOTE:</b> This product supports the four types of data transfer defined by USB: bulk, control, interrupt, and isochronous transfers.		
Connectors	2 LC	
Nominal peak wavelength	850 nm for multimode 1310 nm for singlemode	
Optical loss budget	Singlemode 13 dB, maximum Multimode 7 dB, maximum	
Signal transmission distance	30 km (18.64 miles) with singlemode (SM) cables 300 m (985 feet) with 62.5 µm OM1 multimode (MM) cables 1 km (3280 feet) with 50 µm OM2 multimode (MM) cables 2 km (6541 feet) with 50 µm OM3/OM4 2000 MHz bandwidth laser optimized multimode cables	
USB HUB – RX UNITS		
Number/signal type	(1) 4-port USB hub	
GENERAL		
Power supply	External Input: 100-240 VAC, 50-60 Hz Output: 12 VDC, 1 A	
Cooling	Convection, no vents	
Thermal dissipation	Transmitter Device and power supply Singlemode: 14.8 BTU/hr Multimode: 13.9 BTU/hr Receiver Device and power supply Singlemode: 19.9 BTU/hr Multimode: 18.8 BTU/hr	
Mounting	Rack mount Yes, with optional rack shelf or rack mounting brackets Furniture or wall mount Yes, with optional mounting kits	
Vibration	ISTA 1A in carton (International Safe Transit Association)	
Regulatory compliance	Safety CE, c-UL, KCC, UL EMI/EMC CE, C-tick, FCC Class A, ICES, VCCI Class A Environmental Complies with the appropriate requirements of RoHS, WEEE	
Warranty	3 years parts and labor	
<b>NOTE:</b> All nominal levels are at ±10%.		
<b>Model</b>	<b>Version Description</b>	<b>Part number</b>
FOX T USB Extender Plus MM	Multimode - Transmitter	60-1474-11
FOX T USB Extender Plus SM	Singlemode - Transmitter	60-1474-12
FOX R USB Extender Plus MM	Multimode - Receiver	60-1474-21
FOX R USB Extender Plus SM	Singlemode - Receiver	60-1474-22
FOX T USB Extender Plus HID MM	Multimode - HID Transmitter	60-1526-11
FOX T USB Extender Plus HID SM	Singlemode - HID Transmitter	60-1526-12
FOX R USB Extender Plus HID MM	Multimode - HID Receiver	60-1526-21
FOX R USB Extender Plus HID SM	Singlemode - HID Receiver	60-1526-22

For complete specifications, please go to [www.extron.com](http://www.extron.com)  
Specifications are subject to change without notice.

### WORLDWIDE SALES OFFICES

Anaheim • Raleigh • Silicon Valley • Dallas • New York • Washington, DC • Toronto • Mexico City • Paris • London • Frankfurt  
Stockholm • Amersfoort • Moscow • Dubai • Johannesburg • Tel Aviv • Sydney • Melbourne • New Delhi • Bangalore  
Singapore • Seoul • Shanghai • Beijing • Hong Kong • Tokyo

[www.extron.com](http://www.extron.com)