

Specifications

FOX3 T 301/311

TRUE 4K specification

Max. 4K Capabilities		
Resolution and Refresh Rate	Chroma Sampling	Max. Bit Depth per Color
4096 x 2160 at 60 Hz ¹	4:4:4	8 bit
3840 x 2160 at 60 Hz ¹		
4096 x 2160 at 30 Hz ¹		10 bit
3840 x 2160 at 30 Hz ¹		
4096 x 2160 at 60 Hz ²	4:2:2	12 bit
3840 x 2160 at 60 Hz ²		
4096 x 2160 at 30 Hz ²	4:4:4	
3840 x 2160 at 30 Hz ²		

Frame rate³ 24, 25, 30, 50, or 60 fps
 Chroma sampling³ 4:4:4, 4:2:2
 Color bit depth^{2,3} 8, 10, or 12 bits per color
 Signal type HDMI 2.0, HDCP 2.3
 Max. video data rate 18.0 Gbps

NOTE: ¹Supports lossless 4K video over one fiber or uncompressed 4K video over two fibers.
²Supports 12-bit color bit depth for uncompressed 4K video over two fibers. When using a FOX3 SR scaling receiver, the scaler must be in bypass mode to pass 4K video with a 12-bit color bit depth.
³Subject to the maximum data rate limit. Use our calculator at www.extron.com/8KdataRate to determine video parameters supported by this data rate.

NOTE: This product contains Class 1 laser. It meets the safety regulation of IEC 60825-1, FDA 21 CFR 1040.10, and FDA 21 CFR 1040.11.

Optical fiber interconnection between transmitter and receiver

Number/type 1 or 2 SFPs
 Connectors 1, 2, or 3 LC connectors
 Operating distance
 Singlemode 20 km (12.4 miles) with singlemode (SM) cables
 Multimode 500 m (1640 feet) with 50 μm OM4 4700 MHz bandwidth laser optimized multimode cables

NOTE: The system works with OM1, OM2, and OM3 fiber at reduced distances.

NOTE: Operating distance is approximate. These are typical maximum distances that may vary depending on factors such as fiber type, fiber bandwidth, connector splicing, losses, modal or chromatic dispersion, environmental factors, and kinks.

Nominal peak wavelength 850 nm for multimode, 1310 nm for singlemode

Specifications • FOX3 T 301/311 (Continued)

Data rate.....	10.0 Gbps (1 fiber) or 20.0 Gbps (2 fibers)
Transmission power	
Singlemode	-5.2 dBm, typical
Multimode	-3.3 dBm, typical
Maximum receiver sensitivity	
Singlemode	-12.6 dBm, typical
Multimode	-13.0 dBm, typical
Optical loss budget	
Singlemode	+7.4 dB, maximum
Multimode	+9.7 dB, maximum

Video

Maximum data rate.....	18.0 Gbps (6.0 Gbps per color)
Maximum pixel clock.....	594 MHz
Resolution range.....	640x480 ⁸ up to 4096x2160 ^{1,2,3,4,5,6,7,8} , 480p ^{7,8} , 576p ⁶ , 720p ^{3,4,5,6,7,8,9} , 1080i ^{6,7,8} , 1080p ^{1,2,3,4,5,6,7,8,9} , 2K ^{1,2,3,4,5,6,7,8} , 3840x2160 ^{1,2,3,4,5,6,7,8} , 4096x2160 ^{1,2,3,4,5,6,7,8}
	¹ 23.98 Hz, ² 24 Hz, ³ 25 Hz, ⁴ 29.97 Hz, ⁵ 30 Hz, ⁶ 50 Hz, ⁷ 59.94 Hz, ⁸ 60 Hz, ⁹ 120 Hz
Frame rate	24, 25, 30, 50, 60, or 120 fps
Color space	4:4:4, 4:2:2
Color bit depth.....	8, 10, and, 12 bits per color
Standards	HDMI 2.0, HDCP 2.3
Horizontal frequency	24 kHz to 135 kHz for resolutions up to 18 Gbps
Vertical frequency.....	24 Hz to 120 Hz for resolutions up to 18 Gbps
Format.....	RGB and YCbCr digital video

Video input and loop out

Number/signal type.....	1 HDMI input 1 HDMI loop out
Connectors.....	1 female HDMI input type A 1 female HDMI loop out type A
Power for active cables.....	1.1 W max. for the HDMI port

Audio

Gain.....	Unbalanced output: -6dB; balanced output: 0 dB (default)
Frequency response	20 Hz to 20 kHz, ±0.5 dB
THD + Noise.....	<0.1% @ 20 Hz to 20 kHz at nominal level
S/N.....	>90 dB at maximum output (unweighted)
CMRR.....	65 dB @ 20 Hz to 20 kHz
Stereo channel separation.....	>80 dB @ 1 kHz
Bit depth.....	16, 20, 24
Sampling rate.....	48 kHz

Audio input

Number/signal type.....	1 digital audio, de-embedded from HDMI or 1 analog stereo, balanced/unbalanced
Connectors.....	1 female HDMI (shared with video input) (1) 3.5 mm captive screw connector, 5 pole
Impedance.....	≥10 k ohms unbalanced, ≥20 k ohms balanced
Nominal level.....	+4 dBu (1.23 Vrms), -10 dBV (316 mVrms)
Maximum level.....	+21 dBu balanced, +15 dBu unbalanced
Source formats	2 CH LPCM
Gain range.....	Adjustable, - 18 dB to +24 dB, 1 dB steps

NOTE: 0 dBu = 0.775 Vrms, 0 dBV = 1 Vrms, 0 dBV ≈ 2 dBu

Specifications • FOX3 T 301/311 (Continued)

Audio return output

Number/signal type.....	1 analog stereo, balanced/unbalanced
Connectors.....	(1) 3.5 mm captive screw connector, 5 pole
Impedance.....	50 ohms unbalanced; 100 ohms balanced (analog only)
Maximum level (Hi-Z).....	+21 dBu balanced, +15 dBu unbalanced
Gain error.....	±0.5 dB channel to channel

NOTE: 0 dBu = 0.775 V_{rms}, 0 dBV = 1 V_{rms}, 0 dBV ≈ 2 dBu

Communications

USB configuration port	
Number/type.....	1 front panel mini USB B, female
Standard.....	Ethernet over USB
Serial host control port	
Control.....	1 RS-232, 3.5 mm captive screw connector, 5-pole (3 pins are used), rear panel
Pass-through.....	1 RS-232, 3.5 mm captive screw connector, 5-pole (3 pins are used), rear panel
Baud rate and protocol	
Control.....	9600 baud, 8 data bits, 1 stop bit, no parity
Pass-through.....	9600 to 115,200 baud
Serial control pin configuration.....	Captive screw: 1 = Tx, 2 = Rx, 3 = GND
IR control port.....	(1) 3.5 mm captive screw connector, 5 pole (connector is shared with RS-232 pass thru) TTL level (0 to 5V) modulated infrared control from 30 kHz to 56 kHz
IR control pin configuration.....	3 = GND, 4 = IR Tx, 5 = IR Rx
Ethernet control	
Ethernet port.....	1 RJ-45 connector, female
Ethernet data rate.....	10/100/1000Base-T, half/full duplex with autodetect
Protocols.....	ARP, ICMP (ping), DHCP, DNS, HTTPS, SFTP, SSH, TCP/IP, UDP/IP
Default settings.....	Link speed and duplex level = autodetected IP address = 192.168.254.254 Subnet mask = 255.255.255.0 Gateway = 0.0.0.0 DHCP = off
Program control.....	Extron Product Configuration Software Extron Simple Instruction Set (SIS™)

USB extension

USB standards.....	USB 2.0, USB 1.1
USB data rates.....	Low speed (1.5 Mbps), full speed (12 Mbps), high speed (480Mbps)

USB host ports

FOX3 T 301	
Number/signal type.....	1-port USB HID 1-port USB 2.0
Connectors.....	2 USB type B, female
Maximum built-in USB HUBs....	1
Minimum built-in USB HUBs....	1
FOX3 T 311	
Number/signal type.....	1-port USB HID
Connector.....	1-port USB type B, female
Maximum built-in USB HUBs....	1
Minimum built-in USB HUBs....	1

Specifications • FOX3 T 301/311 (Continued)

General

Power supply	Internal Input: 100-240 VAC, 50-60 Hz
Power consumption	23.3 watts
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Fan, air flows from front to rear (vented)
Thermal dissipation	78.3 BTU/hr
Mounting	
Rack mount	Yes, with optional rack shelf
Furniture mount	Yes, with optional under desk mounting kit
Enclosure type	Metal
Enclosure dimensions	1.7" H x 8.75" W x 8.5" D (half rack wide) (4.4 cm H x 22.2 cm W x 21.6 cm D) (Depth excludes connectors.)
Product weight	2.4 lbs (1.1 kg)
Regulatory compliance.....	CE, c-UL, C-tick, FCC Class A, ICES, UL, VCCI Complies with the appropriate requirements of RoHS, WEEE.
Product warranty	3 years parts and labor
Everlast power supply warranty.....	7 years parts and labor

NOTE: All nominal levels are at $\pm 10\%$.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

5437-D3