

Specifications

IPL EXP RIO8

Memory

SDRAM.....	512 MB
Flash.....	512 MB

Software

Configuration software	Global Configurator® Plus and Professional
Programming software.....	Global Scripter®
Control apps.....	Extron Control, iGVE
Resource management software....	GlobalViewer® Enterprise
Utilities	Toolbelt, embedded web page

Ethernet

Network interface controllers (NICs)	1
Connectors.....	1 female RJ-45 connector
Data rate.....	10/100Base-T, half/full duplex with autodetect
Protocols	DHCP, DNS, HTTP (redirect), HTTPS, ICMP (ping), IEEE 802.1X, NTP, SFTP, SNMP, SSH, TCP/IP, UDP/IP
Default settings	Link speed and duplex level = autodetected IP address = 192.168.254.250 Subnet mask = 255.255.255.0 Gateway = 0.0.0.0 DHCP = off DNS = 127.0.0.0

Digital I/O

Quantity/type	8 digital input/output (configurable)
Connectors.....	(4) 3.5 mm captive screw connectors, 5 pole
Digital inputs	
Input voltage range.....	0 to 24 VDC, clamped at +30 VDC
Input impedance	>10k ohms
Programmable pullup	1k ohms to +5 VDC
Threshold low to high	2.8 VDC
Threshold high to low	2.0 VDC
Digital outputs.....	250 mA sink from 24 VDC max.
12 VDC, 24 VDC outputs.....	Aggregate power output: 19 watts
Pin configuration	1, 2 = digital I/Os; 3 = 12 VDC; 4 = 24 VDC; 5 = Gnd

Relays

Quantity/type	8 normally open relays
Relay control connectors	(4) 3.5 mm captive screw connectors, 4 pole
Relay control contact rating.....	24 VDC, 1 A

Specifications • IPL EXP RIO8 (Continued)

General

Power supply	Not included
Power input requirements	Power over Ethernet Plus (PoE+) (complies with PoE 802.3af, class 3); 56 VDC (PoE), minimum 0.8 A
Power consumption	
Device	26.9 watts, 56 VDC (PoE+)
Device and PoE injector.....	31.5 watts, 100-240 VAC, 50-60 Hz
Temperature/humidity	Storage: -40 to +158 °F (-40 to +70 °C) / 10% to 90%, noncondensing Operating: +32 to +122 °F (0 to +50 °C) / 10% to 90%, noncondensing
Cooling	Convection, no vents
Thermal dissipation	
Device	26.9 BTU/hr
Device and PoE injector.....	42.5 BTU/hr
Mounting	
Rack mount.....	Yes, with optional 1U rack shelf or back of the rack mounting kit
Furniture mount	Yes, with optional bracket kit
Enclosure type	Metal
Enclosure dimensions	1.7" H x 4.3" W x 6.0" D (1U high, quarter rack wide) (43 mm H x 109 mm W x 152 mm D)
Product weight	0.45 lbs (0.2 kg)
Regulatory compliance.....	CE, C-Tick, c-UL, FCC Class A, ICES, UL, VCCI Complies with the appropriate requirements of RoHS, WEEE
Warranty	3 years parts and labor

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

NOTE: Shipping weights and dimensions are available at www.extron.com.

5297-D2