

DATA SHEET

DESONO™ P6

PENDANT LOUDSPEAKER

The desono™ P6 is a two-way passive coaxial loudspeaker intended for full range music reproduction in distributed audio applications. It delivers high intelligibility coupled with a wide coverage area; designers can use fewer speakers in a space while maintaining acceptable levels of speech intelligibility.

The desono P6 utilizes a 6-position switchable transformer ranging from 1.875W to 60W with low-impedance bypass for constant-voltage operation, making it an excellent choice for large areas of BGM.

Designed with the installer in mind, the P6 is mechanically steerable, allowing up to 10° pitch, directing the audio where it's needed.

The desono P6 is rated for outdoor splash applications such as patios or concourses, and an ideal choice for both indoor and outdoor distributed audio applications that demand superior speech intelligibility and full range music reproduction.



FEATURES

- 60W continuous output with a peak power of 240W
- Traditional “raindrop” profile
- 6-ohm nominal impedance
- 130° coverage angle
- 6-position constant voltage tap (1.875W, 3.75W, 7.5W, 15W, 30W, 60W) with low impedance bypass
- Mechanically steerable; allows up to 10° pitch
- Bridge-mounted 1-inch (25mm) soft dome tweeter
- 6.5-inch (165mm) polypropylene woofer mechanically isolated from the high frequency driver
- Suitable for indoor and outdoor use
- CE marked, UL listed, and RoHS compliant
- Covered by Biamp Systems' five-year warranty


ARCHITECTS & ENGINEERS SPECIFICATIONS

The pendant loudspeaker shall be a two-way, passive coaxial design intended for overhead mounting. The pendant loudspeaker shall be equipped with a 6.5 inch (165mm) polypropylene low frequency transducer (“woofer”), a 1 inch (25mm) soft dome high frequency transducer (“tweeter”), and a passive crossover/protection circuit network. The high-frequency transducer shall be physically separate from the low frequency transducer and shall be bridge-mounted above the low frequency transducer. The pendant loudspeaker shall have a nominal impedance of 6 ohms. The pendant loudspeaker shall have a coverage angle of 130° from 1kHz to 6kHz. The pendant loudspeaker enclosure shall be constructed of formed steel and UL94V-0 fire rated plastic. The pendant loudspeaker shall maintain an IP34 rating. The pendant loudspeaker shall have an attachment point for connection via chain or wire to building structure as a support point. The pendant loudspeaker shall be mechanically steerable, allowing for up to a 10° pitch. The pendant loudspeaker shall comply with the requirements of UL Standard 1480a and UL Standard 2043. The pendant loudspeaker shall be UL listed, CE marked, and shall be compliant with the RoHS directive. Warranty shall be seven years. The pendant loudspeaker shall be desono™ P6.

DESONO P6 SPECIFICATIONS

DIMENSIONS

Connectors:	TBD
Nominal Impedance:	6Ω
Transducers:	
Low Frequency:	6.5-inch (165 mm) polypropylene cone woofer
High Frequency:	1-inch (25 mm) plastic dome bridge-mounted tweeter
Frequency Range (-10dB):	60Hz — 20kHz
Output Power Rating (3dB compression, pink noise):	60W continuous; 240W peak
Sensitivity (1W @ 1m):	> 88dB SPL
Maximum SPL:	TBD
Nominal Coverage Angle (1-6kHz):	130°
Operating Environment:	Designed for Indoor/Outdoor Use
Included Accessories:	Hanging hardware; Dust cover
Product Dimensions:	
Overall Diameter:	9.4 inches (238mm)
Depth:	15.6 inches (397mm)
Weight:	TBD
Compliance:	UL and C-UL listed (USA and Canada) CE Marked (Europe) RoHS Directive (Europe)



Biamp, desono, and Tesira are either trademarks or registered trademarks of Biamp Systems, LLC in the United States and other countries. Other product names referenced may be trademarks or registered marks of their respective owners and Biamp Systems is not affiliated with or sponsored by these companies.