

Specifications

XTP CrossPoint® CP Audio Output Board

Audio output — XTP CP 4o SA

| | |
|-------------------------------|---|
| Connectors | (4) 3.5 mm captive screw connector, 5 pole |
| Number/signal type..... | 4 stereo, balanced/unbalanced |
| Impedance..... | 50 ohms unbalanced, 100 ohms balanced |
| Gain error..... | ±0.1 dB channel to channel |
| Maximum level (Hi-Z)..... | >+21 dBu, balanced or unbalanced at 0.1% THD+N |
| Maximum level (600 ohm) | >+20 dBm, balanced or unbalanced at 0.1% THD+N |
| Volume control range | -75.8 to 0 dB (volume numbers 0 through 64) in a 35 dB increment from step 0 to step 1, then in 1 dB increments from steps 1 to 64; default = 64 (0 dB) |

NOTE: Attenuation = volume number minus 64. The default is 0 dB = volume number 64.

General

| | |
|------------------------|---|
| Power | Supplied by XTP CrossPoint or XTP II CrossPoint enclosure |
| Power consumption..... | 5 watts |
| Product weight | 2.0 lbs (0.9 kg) |
| Regulatory compliance | |
| Environmental..... | Complies with the appropriate requirements of RoHS, WEEE. |
| Warranty | 3 years parts and labor |

NOTE: All nominal levels are at ±10%.

NOTE: Specifications are subject to change without notice.

8.1-030316-D2